

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

DOP Number: 223 Revison:

Product type: SC60b

<u>Intended use:</u> : To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

## **Declared Performance:**

Essential Characteristics	Performance	
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)	
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)	
Water Absorption	Zero	
Water Vapour Permeability	Not Applicable	
Thermal Resistance	Steel 64 W / m.k	
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A	
Durability (against corrosion)	st corrosion) Coating L14	
Durability (against freeze/thaw)	Resistant	
Dangerous Substance	None	
Minimum Bearing Length (mm)	150 mm	

Nominal Height (mm)	146.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	17.3
Load Ratio	1:1 - 1:19

	Clear Opening span (mm)	SWL UDL (kN)
	600	40
	750	40
	900	40
	1050	38
	1200	34
	1350	30
	1500	28
	1650	26
	1800	24
	1950	22
ı	2100	21
ı	2250	19
ı	2400	18
ı	2550	17
ı		
ı		
ı		
ı		
l		
l		
l		
l		

TableA1:

Load bearing capacity

## Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)