



# Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 228

Revision:

Product type: EAL6 60

Intended use: : To be used in walls and partitions, as an ancillary components for masonry  
(*BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure*)

**Manufacturer:**

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

**The Notified Testing Laboratory:**

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

**This DOP is covered by following harmonised standard:**

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

**TableA1:  
Load bearing capacity**

Clear Opening span (mm)	SWL UDL (kN)
600	183
900	183
1200	183
1500	183
1800	183
2100	183
2400	183
2700	183
3000	183
3300	167
3600	154
3900	142
4200	123
4500	107

**Declared Performance:**

Essential Characteristics	Performance
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

hEN  
EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

Nominal Height (mm)	238.0
Mass per unit area (kg/m <sup>2</sup> )	NPD
Mass (kg/m)	61.2
Load Ratio	1:1 - 1:19

**Note:**

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :  Harvey Steel 01.07.2013  (Place and date of issue)	David Harvey (Managing director)    (Signature)
---	---