

Declared Performance:

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number:267Product type:SC90bIntended use:To be u

Revison:

TableA1:

Clear Opening

600

750

900

1050

1200

1350

1500

1650

1800

1950

2100

2250

2400

2550

2700

span (mm)

Load bearing capacity

SWL UDL

30

30

30

30

30

30

28

25

23

22

20

19

18

17

16

(kN)

To be used in walls and partitions, as an ancillar components for masonry (BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

<u>The Notified Testing Laboratory:</u> University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Essential Characteristics	Performance	hEN
Load Bearing Capacity (E_k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed	
	loading (UDL)	<u> </u>
Deflection Under Load	Less than effective span/325 as safe working load in service limit state	s fo
	(EN 1990: 2002 + A1 ; 2005 NA)	Jent
Water Absorption	Zero	ıodu
Water Vapour Permeability	Not Applicable	COI
Thermal Resistance	Steel 64 W / m.k	illary
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A	anci
Durability (against corrosion)	Coating L14	Specification for ancillary components for Lintels
Durability (against freeze/thaw)	Resistant	atior
Dangerous Substance	None	cific els
Minimum Bearing Length (mm)	150 mm	Specifi Lintels
		2012, ^{>} art 2:
Nominal Height (mm)	139.0	—
Mass per unit area (kg/m ²)	NPD	5 - 2 ary -
Mass (kg/m)	17.1	EN 845 - 2 masonary
Load Ratio	1:1 - 1:5	EN

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

David Harvey (Managing director)

(Place and date of issue)

(Signature)