

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 279 Revison:

Product type: EAL6 90E

<u>Intended use:</u> : To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics Performance Load Bearing Capacity (Ek, in kN) Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL) Deflection Under Load Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1; 2005 NA) Water Absorption Zero Water Vapour Permeability Not Applicable Thermal Resistance Steel 64 W / m.k NPD (Contact Harvey steel for project specific details) document A Resistance to Fire Coating L14 Durability (against corrosion) Durability (against freeze/thaw) Resistant Dangerous Substance None Minimum Bearing Length (mm) 150 mm

Nominal Height (mm)	234.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	62.5
Load Ratio	1:1 - 1:19

hE	N
N 845 - 2: 2012, Specification for ancillary components for	asonary - Part 2: Lintels

Clear Opening span (mm)	SWL UDL (kN)
600	184
900	184
1200	184
1500	184
1800	184
2100	184
2400	184
2700	184
3000	184
3300	168
3600	155
3900	143
4200	127
4500	111

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)