

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

DOP Number: 351 Revison:

Product type: SC150EEa

<u>Intended use:</u> : To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

## **Declared Performance:**

Essential Characteristics	Performance
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	153.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	28.4
Load Ratio	1:1 - 1:5

hE	- NI
ne	:IN
s for	
ß	
eu	
G	
ď	
ĕ	
>	
<u></u>	
nci	
ā	
Q	
o	
ä	
ij	S
မ္	ntels
Sp	•=
ζ,	art 2: I
5	art
2 : 2012, Specification for ancillary components for	Ο.
:N 845 - 2 : 2012, Specifica	nasonary - F
5	g
8	S
z	g

Clear Opening span (mm)	SWL UDL (kN)
600	39
750	39
900	39
1050	39
1200	39
1350	39
1500	39
1650	39
1800	39
1950	36
2100	34
2250	31
2400	30
2550	28
2700	26

TableA1:

Load bearing capacity

## Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)