

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

DOP Number: 395 Revison:

Product type: Box 140-150

<u>Intended use:</u> : To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA)
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

## **Declared Performance:**

| Essential Characteristics                      | Performance   |
|--|---|
| Load Bearing Capacity (E <sub>k</sub> , in kN) | Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)                    |
| Deflection Under Load                          | Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA) |
| Water Absorption                               | Zero  |
| Water Vapour Permeability                      | Not Applicable  |
| Thermal Resistance                             | Steel 64 W / m.k  |
| Resistance to Fire                             | NPD (Contact Harvey steel for project specific details) document A                                      |
| Durability (against corrosion)                 | Coating L14   |
| Durability (against freeze/thaw)               | Resistant   |
| Dangerous Substance                            | None  |
| Minimum Bearing Length (mm)                    | 150 mm  |

| Nominal Height (mm)        | 143.0 |
|----------------------------|-------|
| Mass per unit area (kg/m²) | NPD   |
| Mass (kg/m)                | 14.9  |
| Load Ratio                 | -     |

| hE   | - NI         |
|--|--------------|
| ne   | :IN          |
|  |              |
|  |              |
| s for  |              |
| ß  |              |
| eu   |              |
| G  |              |
| ď  |              |
| ĕ  |              |
| >  |              |
| <u></u>  |              |
| nci  |              |
| ā  |              |
| Q  |              |
| o  |              |
| ä  |              |
| ij   | S            |
| မွ   | ntels        |
| Sp   | •=           |
| ζ,   | art 2: I     |
| 5  | art          |
| 2 : 2012, Specification for ancillary components for | Ο.           |
| :N 845 - 2 : 2012, Specifica                         | nasonary - F |
| 5  | g            |
| 8  | S            |
| z  | g            |

| Clear Opening<br>span (mm) | SWL UDL<br>(kN) |
|----------------------------|-----------------|
| 600                        | 60              |
| 750                        | 60              |
| 900                        | 60              |
| 1050                       | 60              |
| 1200                       | 60              |
| 1350                       | 60              |
| 1500                       | 60              |
| 1650                       | 60              |
| 1800                       | 55              |
| 1950                       | 50              |
| 2100                       | 50              |
| 2250                       | 45              |
| 2400                       | 40              |
| 2550                       | 35              |
| 2700                       | 30              |
| 2850                       | 30              |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |
|                            |                 |

TableA1:

Load bearing capacity

## Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)