



Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 340

Revision: a

Product type: MC150B

Intended use: To be used in walls and partitions, as an ancillary components for masonry
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels
Commerce way, Whitehall Industrial Estate
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,
Research and Environmental Applications (CEREA)
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003.
European Harmonised Standard EN 1090-1 :2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1:2009
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	232.0
Mass per unit area (kg/m ²)	NPD
Mass (kg/m)	25.9
Load Ratio	1:1 - 1:19

hEN
EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

TableA1: Load bearing capacity	
Clear Opening span (mm)	SWL UDL (kN)
600	60
750	60
900	60
1050	60
1200	60
1350	60
1500	60
1650	60
1800	60
1950	60
2100	60
2250	60
2400	60
2550	60
2700	60
2850	60
3000	58
3150	55
3300	53
3450	50
3600	48
3750	47
3900	45
4050	43
4200	41
4350	38
4500	36

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :
Harvey Steel 01.01.2025
(Place and date of issue)

Michael Polley (General Manager)